



DuPont Automotive Finishes

DuPont™ Sanding Paste 2311S™

Description

DuPont™ Sanding Paste 2311S™ is designed for preparing body panels for basecoat blends. It will allow the technician to abrade the repair surface efficiently with the yellow color giving a good visual aid in tracking the work. An added benefit to DuPont™ Sanding Paste is the residue can be removed effectively with water. Using 2311S™ will help minimize problems in panel preparation which can lead to poor blends.

General Information

Components

DuPont™ Sanding Paste 2311S™

Mix Ratio/Viscosity

Ready to use.

Application

Substrate

Properly prepared OEM finish.

Surface Preparation

Prepare the repair area according to the Surface Prep guidelines in the General Procedures section. Perform repair using primer or sealer as necessary.





DuPont Automotive Finishes

DuPont™ Sanding Paste 2311S™

DuPont™ 2311S™ cleaning paste can be used with a damp ultra fine scuff pad. Apply a small amount of paste; a dab the size of a quarter will do to start.

Step 1: Sand blend area using a scuff pad and sanding paste. Be sure not to let the sanding paste dry on the body panel.

Step 2: Scrub and rinse with clean water making sure to remove all paste residue.

Tips for Success

Use a small a small stiff brush to sand around difficult to reach places such as moldings

Physical Properties

VOC LE:	1.1	lb/gal
VOC AP:	0.5	lb/gal
Weight per gallon:	12.4	lb/gal
Flash Point:	See MSDS.	

VOC Regulated Areas

These directions refer to the use of products which may be restricted in VOC regulated areas. Follow usage recommendations in the VOC Compliant Products Chart for your area.

Safety and Handling

Before using any DuPont Refinish product, be sure to read all safety directions and warnings. WEAR A PROPERLY FITTED AIR PURIFYING RESPIRATOR with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A), eye protection, gloves and protective clothing during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air purifying respirator fit is not possible, wear a positive-pressure, supplied air respirator (NIOSH TC-19). In all cases follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. This product is intended for industrial use only by professional, trained painters.

Please visit: www.performancecoatings.dupont.com to view or print an addition copy of this "Technical Product Data" sheet.