

U-POL

PRODUCTS

GRAVI-TINT

TINTABLE HS STONE CHIP PROTECTOR

FEATURES & BENEFITS	<ul style="list-style-type: none">GRAVI-TINT is a 1L tintable stone chip protector. The neutral base can be tinted using the color pigments from U-POL's Colour Match Primer System.GRAVI-TINT allows users to create ANY colour stone chip protector (even difficult dark shades), using U-POL's Colour Match Tinter Pigments.GRAVI-TINT provides value for money - the coloured ground coat reduces the amount of top coat paint required.GRAVI-TINT saves time – less top coat colour needs to be applied.GRAVI-TINT is tough, hard and durable and is formulated to reproduce the manufacturers original stone chip finish.GRAVI-TINT protects against stone chips, salt, damp and rust and also helps to deaden sound and vibrations and is, therefore it is ideal for application to panels and inside engine compartments.GRAVI-TINT's high build formula will cover weld marks and seams, often in one application.GRAVI-TINT reduces the visibility of stone chips in the top coat, once applied.GRAVI-TINT is fast drying & can be over painted rapidly with most paint systems.GRAVI-TINT is ready for use and is fast, effective & easy to apply.
--------------------------------	---

SURFACE PREPARATION & INSTRUCTIONS FOR USE	<p>GRAVI-TINT tintable stone chip protector can be used on the following surfaces:-</p> <ul style="list-style-type: none">Suitably prepared bare metal. For overcoating aluminium, ACID #8 etch primer is recommended.Original paint surfaces (with the exception of thermoplastic acrylics). <p>Thoroughly clean and degrease old paint surfaces with a suitable spirit wipe or reducer. Wet sand with 400 grade paper. For bare metal use 180 grade paper. Re-clean and dry.</p>
---	--

APPLICATION	<ol style="list-style-type: none">1. Use the Colour Match Wheel provided to determine the shade of colour required.2. Knead the tint(s) required & add into the GRAVI-TINT Bottle.3. Shake the bottle thoroughly for a minute. GRAVI-TINT is now ready to use.4. Apply with a clean Schutz gun or brush. Allow approximately 10-15 mins. for the solvent to flash off when building a thick coat. <p>NOTE:</p> <ol style="list-style-type: none">1. GRAVI-TINT SHOULD ALWAYS BE USED IN CONJUNCTION WITH THE COLOUR MATCH TINTS.2. WE RECOMMEND THAT PIGMENT ADDITION DOES NOT EXCEED 4% BY WEIGHT.
--------------------	--

REDUCERS	<p>HS GRAVITEX PLUS is supplied ready for use. However, up to 5% of good quality urethane reducers may be added to vary the texture. Use urethanereducers or similar proprietary products to clean the gun after use.</p>
-----------------	---

U-POL

P R O D U C T S

BUILD & PRESSURE	One coat of GRAVI-TINT will give a build of approximately 100-150 microns and a pressure of between 2.76 - 4.82 BAR is required at the gun. Less or more pressure will give a flatter or more rippled effect.
-----------------------------	--

DRYING TIME	Approximately 2 hours at normal shop temperature or 30 mins. at low bake (80°F). Drying time is dependent on film thickness, humidity and temperature.
--------------------	--

OVER-PAINTING	GRAVI-TINT may be over-painted with most paint systems. With 2 pack acrylic paints its can be over-painted wet on wet. For optimum gloss and durability the use of a primer is recommended.
----------------------	--

PRODUCT CODES	Order Code	Size	Case Quantity	Product Description
	UP0734	1L	12	GRAVI-TINT – Tintable HS Stone Chip Protector (Neutral Base)
	UP2500	27ml	20	Colour Match Tinter Pigments – WHITE
	UP2510	40ml	20	Colour Match Tinter Pigments – YELLOW
	UP2520	40ml	20	Colour Match Tinter Pigments – BLUE
	UP2530	40ml	20	Colour Match Tinter Pigments – BLACK
	UP2540	40ml	20	Colour Match Tinter Pigments – RED
	n/a	n/a	n/a	Colour Match Disk