



LIMCO

New Product Bulletin

LS800 Sealer

Limco Product management is pleased to announce the introduction of our newest 2K undercoating: LS800 Sealer. LS800 is a tintable wet-on-wet sealer that dries quickly and provides excellent adhesion. LS800 Sealer can be tinted using either Limco1-2-3-4 bases or Limco Supreme bases.

As a wet-on-wet sealer, LS800 is a welcome addition to the Limco line that will aid technicians in performing timely and economical repair procedures. LS800 can be directly applied to properly sanded OEM finishes or spare parts, fiberglass and body fillers, as well as pretreated steel and aluminum. LS800 is tintable for improved color holdout and hiding, and it flashes off in only 15 minutes when mixed with Limco bases. LS800 can also be flexed for use over bumpers and other flexible body parts.

- Wet-on-wet application
- 15 minute flash with Limco 1-2-3-4 bases
- Flexible ratio

LS800 uses the LH400 series hardeners and can be sprayed at either 4.6 VOC or 3.5 VOC through choice of reducer. The mix ratios are simple – mix 4:1:2 untinted and 4:1:1:2 tinted. Do not use ready-for-use Limco or Supreme color when mixing.

KLINER'S – KEEPING YOU INFORMED

ALLENTOWN: 1-610-433-3203 / HAZLETON: 1-570-454-7616 / PHILLIPSBURG: 1-908-859-5911
POTTSVILLE: 1-570-622-4010 / READING: 1-610-929-4737 / SCRANTON: 1-570-344-8516
STROUDSBURG: 1-570-424-2253