



DuPont A-7480S™ Acrylic Trim & Jamb Clear

Description

DuPont A-7480S™ Acrylic Trim & Jamb Clear is an easy to use ready-to-spray Acrylic Trim & Jamb Clear designed for cosmetic repairs. This aerosol clear is designed to be versatile and have excellent application and appearance for a 1K acrylic clear.


DuPont A-7480S™ Acrylic Trim & Jamb Clear is conveniently packaged in an aerosol container to deliver

- Quick Dry
- High Gloss
- Convenient, Easy Application

General Information


Components

DuPont A-7480S™ Acrylic Trim & Jamb Clear



Mix Ratio/Viscosity


Ready to use.



Application

Substrates

Sanded substrates
 OEM finishes
 Cured, repainted surfaces
 Sanded primers




Surface Preparation

For application over properly prepared basecoat:

- Mask the repair area to prevent overspray from sticking
- Allow basecoat to dry 15 - 30 minutes prior to application of the 1K Acrylic Clear.



DuPont A-7480S™ Acrylic Trim & Jamb Clear



Application


Shake aerosol for 2 minutes to ensure contents are uniformly mixed.

- Step 1: Apply two medium-wet coats of the DuPont A-7480S™ Acrylic Trim and Jamb Clear to prepared basecoat.
- Step 2: Allow 10 - 15 minutes flash time between coats.



Tips for Success:

- DuPont Acrylic Clear A-7480S™ Acrylic Trim & Jamb Clear primarily recommended for cosmetic repairs.



Flash/Dry Times

Air Dry

Flash Between Coats:	10 - 15 minutes
Dust Free	30 minutes at 70°F (20°C)

Physical Properties

VOC: LE	4.972 lbs/gal ready to use in aerosol container
AP	4.236 lbs/gal ready to use in aerosol container
PWMIR Value:	1.32
Flash Point:	See MSDS.

VOC Regulated Areas

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing and usage recommendations in the VOC Compliant Products Chart for your area.

Safety and Handling

Before using any DuPont Refinish product, be sure to read all safety directions and warnings. WEAR A PROPERLY FITTED AIR PURIFYING RESPIRATOR with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A), eye protection, gloves and protective clothing during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air purifying respirator fit is not possible, wear a positive-pressure, supplied air respirator (NIOSH TC-19). In all cases follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. This product is intended for industrial use only by professional, trained painters.

DANGER! EXTREMELY FLAMMABLE. Do not spray near sparks, heat or open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are exhausted. Do not use on plastic or fiberglass substrates due to possible static build-up which MAY CAUSE FLASH FIRE.

WARNING CONTENTS UNDER PRESSURE. Do not puncture, incinerate, burn or store above 120°F. FOR MORE INFORMATION, REFER TO MATERIAL SAFETY DATA SHEET