

SEALERS & FOAMS



SEALERS AND FOAMS

The PLIOGRIP by Valvoline high-performance line of Sealers and Foams provides body shops with a complete package to finish the repair.

PLIOGRIP by Valvoline Sealers and Foams are easy to work with and yield fantastic results:

- 1K Seam Sealer – A permanently flexible, moisture-cured seam sealer for standing seams, floor pans, trunks, wheel wells and more, for an OEM-matching brushed, bead or sprayed texture
- 2K Seam Sealer – our new 2K epoxy seam sealers can be painted immediately
- Rigid and Flexible Foam – Rigid and flexible NVH foams with 5 seconds of work time or less, these foams match OEM materials without unwanted structural pressure

All PLIOGRIP by Valvoline Sealers and Foams offer excellent adhesion, no shrinkage and a lifetime warranty.

THE SYSTEM

Our Sealers and Foams are part of a family of versatile, fast-acting, smooth-finishing PLIOGRIP by Valvoline products.

PLIOGRIP by Valvoline. Easier to use. Faster to cure. Proven to perform.

SEALERS

- Easy to tool out
- Non-sag, no shrinkage
- Excellent adhesion to primed metal
- Lifetime warranty

FOAMS

- 10x expansion
- Excellent adhesion to primed metal
- No shrinkage or unwanted structural pressure
- Lifetime warranty
- Non-flammable

Product	Application	Sizes	Stock No.	Work Time	Sand Time	Paint Time
Non-Sag Seam Sealer 6	Non-sag 2K seam sealer. Duplicates OEM tape and brushed seams.	220ml	8008	6 minutes	30 minutes	Immediately, scuff after 30 minutes.
High-Body Seam Sealer 12	Non-sag 2K seam sealer. Duplicates OEM tapes and brushed seams.	220ml	8009	12 minutes	30 minutes	Immediately, scuff after 30 minutes.
Self-Leveling Seam Sealer 12	Self-leveling sealer. Duplicates OEM puddle seams and roof ditches.	220ml	8010	12 minutes	30 minutes	Immediately, scuff after 30 minutes.
Controlled-Flow Seam Sealer 6	Higher body flowable sealer for tape seams with round edges often seen on imports.	220ml	8050	6 minutes	30 minutes	Immediately, scuff after 30 minutes.
Flexible PUR Sealer	White, flexible 1K non-sag seam sealer. Duplicates OEM taped and brushed seams	310ml tube	8011	20 minutes	N/A	Immediately – 6 hours.
Sprayable MSP Sealer	Black or White, sprayable 1K textured spray seam sealer. Duplicates OEM wheel wells, trunk, floor pan, and apron seams.	310ml tube (black) 310ml tube (white)	8012 8013	20 minutes	N/A	Immediately – 4 days.
NVH Flexible Foam	Black expandable foam for intrusion beams and rockers. Duplicates OEM applications.	220ml	8014	3-10 second Foam Time	N/A	N/A
NVH Rigid Foam	Cream color expandable foam for pillars. Matches OEM materials without unwanted structural pressure.	220ml	8015	10-15 second Foam Time.	N/A	N/A

All data taken at 23°C (74°F)

BODY REPAIR SYSTEM FROM ASHLAND

©Registered trademark, Ashland. ©Copyright 2007, Ashland. (R9/07) www.pliogripbyvalvoline.com