



PRODUCT INFORMATION SHEET

SEAM SEALERS

PRODUCT: MAXIM™ New MSX SEAM SEALER

PART NUMBER: 100825 Cartridge 10.3 oz. (305 mL) 12 units/case 13 lbs/case

DESCRIPTION: Maxim™ MSX Seam Sealer is a sprayable, brushable and beadable seam sealer formulated to duplicate automotive OEM coarse textured and beaded seams. MSX has excellent adhesion to primed painted metal, galvanized steel, rigid plastics, fiberglass and aluminum. Contains no silicone. Easily duplicates OEM sprayable seam sealers when applied with Evercoat's #827 Sprayable Seam Sealer Applicator. As a beadable seam sealer, Maxim™ MSX Seam Sealer has excellent tooling characteristics and sag resistance.

TECHNICAL SPECIFICATIONS:

- **Appearance** Beige
- **VOC** None
- **Working Time** 25 minutes @ (72°F/22°C)
- **Paint Time** 30 minutes
- **Full Cure** – 24 hours
- **Contents and Cautions** – MSDS available upon request or at evercoat.com

FEATURES & BENEFITS

- Easy to use
- Excellent gunability
- Sprayable, brushable, and beadable
- Excellent adhesion to many substrates
- Non-sag
- Can be directly topcoated in 30 minutes
- Can be baked immediately after topcoat is applied
- Unaffected by solvents after cure

PREPARATION:

- Clean area with a mild solvent cleaner and a clean rag to remove grease, oils and other contaminants. Wipe with a dry rag.
- Sand area with 180-220 grit sand paper. Do not remove factory E-coat.
- Apply primer surfacer according to paint manufacturer's recommendation.
- Sand primer surfacer with 320-grit sand paper.
- Blow area to remove dust using compressed air.
- Re-clean with a mild solvent cleaner.

APPLICATION:

Bead Type

Apply steady pressure to the caulking gun at all times during application. Tool the Maxim™ MSX Seam Sealer to match the OEM seam. Mild solvent may be used to smooth the surface. Allow to dry for 30 minutes at 72°F before topcoating. Thicker applications may require longer dry times.

If applying with the Evercoat #827 Sprayable Seam Sealer Applicator, refer to **Tech Tip 350-MSS-TT3** and **350-MSS-TT4**.

Sprayable

Refer to **Product Information Sheet 350-MSS-PIS4** (Evercoat Sprayable Seam Sealer Applicator) and **Tech Tip 350-MSS-TT3** and **350-MSS-TT4**.

KLINE'S – KEEPING YOU INFORMED

ALLENTOWN: 1-610-433-3203 / **HAZLETON:** 1-570-454-7616 / **PHILLIPSBURG:** 1-908-859-5911
POTTSVILLE: 1-570-622-4010 / **READING:** 1-610-929-4737 / **SCRANTON:** 1-570-344-8516
STROUDSBURG: 1-570-424-2253