

MATERIAL SAFETY DATA SHEET

Page 1

EFFECTIVE DATE: 02/11/05

SUPERCEDES: 01/06/03

MANUFACTURED FOR: KLINE'S AUTOMOTIVE
630 N. 13th Street
Allentown, PA. 18102
610-433-3203

CHEMTREC: 1-800-424-9300

SECTION 1: GENERAL INFORMATION

PRODUCT NAME: Fast Wax

PRODUCT ID: KCPRFW

NFPA 704

HAZARD RATING

4=Severe H=1

3=Serious F=2

2=Moderate R=0

1=Slight

0=Minimal

SECTION 1A: D.O.T. SHIPPING INFORMATION

Proper Shipping Name: NON-REGULATED MATERIAL*

Hazard Class: N/A

UN/NA: N/A

Packaging Group: N/A

NOTE: N/A = NOT APPLICABLE

* Not regulated when shipped in non-bulk quantities via ground transport only.

EMERGENCY OVERVIEW

WARNING! Combustible liquid and vapor. Harmful if swallowed. May cause eye and skin irritation. Mist or vapor may irritate the respiratory tract. Avoid contact with eye and skin. Avoid breathing vapor or mist. Do not ingest. Wash thoroughly after handling. Keep away from heat, sparks, open flames and oxidizers. Use adequate ventilation.

SECTION 2: HAZARDOUS INGREDIENTS

#	INGREDIENT	CAS #	OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling	ACGIH TLV (ppm or *mg.M ³) +=skin, c=ceiling	WEIGHT %
1	Petroleum Distillates	8052-41-3	500	100	20-40
2	Aminofunctional Siloxane	71750-80-6	N/A	N/A	1-10
3	Amides, tall-oil fatty, N,N-bis (hydroxyethyl)	68155-20-4	N/A	N/A	1-5

SECTION 5: FIRE AND EXPLOSION DATA

FLASH POINT: 124F TEST: SETA Flash Closed Cup (ASTM D3278)
EXPLOSIVE LIMITS: LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: Use water spray, dry chemical, CO2 or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion may produce noxious and irritating gases which will require fresh air source in fire fighting.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

SECTION 6: REACTIVITY DATA

STABILITY: Stable HAZARDOUS POLYMERIZATION: Does not occur.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, oxidizing agents and excessive heat.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon, Nitrogen, Sulfur and other toxic gases.

SECTION 7: HEALTH HAZARD (ACUTE/CHRONIC)

CARCINOGENICITY: NTP: N IARC: N OSHA: N
EFFECTS OF OVEREXPOSURE:
EYES: May cause mild temporary eye irritation.
SKIN: May cause mild temporary skin irritation. Repeated or prolonged contact can produce moderate irritation.
INHALATION: Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. May cause central nervous system (CNS) depression including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. Breathing high concentrations of vapor in and enclosed space or by intentional abuse, can cause irregular heartbeats which can cause death.
INGESTION: Harmful if swallowed. May cause mouth, throat, and esophagus irritation. Petroleum distillates can be readily absorbed by the stomach and intestinal tract. Symptoms may include a burning sensation, vomiting, nausea, dizziness, loss of consciousness, and delirium as well as CNS effects.
CHRONIC EFFECTS AND MEDICAL CONDITIONS: Repeated or prolonged occupational overexposure to solvents has been associated with irreversible brain and nervous system damage. May aggravate pre-existing skin, respiratory, liver, kidney or CNS disorders.

SECTION 8: EMERGENCY AND FIRST AID

EYES: Flush with water for a minimum of 15 minutes. Consult a physician.
SKIN: Wash exposed area with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops.
INHALATION: Remove to fresh air. If breathing is difficult consult a physician.
INGESTION: Call physician immediately. Only induce vomiting at the direction of a physician.

SECTION 9: PERSONAL PROTECTIVE MEASURES

EYE PROTECTION: Wear eye protection when chemical contact with eyes is possible. Contact lenses should not be worn.
PROTECTIVE GLOVES: When prolonged or repeated contact is possible, chemical resistant clothing (i.e. gloves) is recommended.

RESPIRATORY PROTECTION: Not required in most applications. Use NIOSH/MSHA approved respiratory protection if high concentrations of vapor or mist are generated.
VENTILATION: Either local exhaust or general room ventilation is recommended.
OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 10: SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Handle according to good manufacturing and warehousing practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove contaminated clothing and wash before reuse. Store in original containers away from heat, sparks, open flames, strong acids or strong oxidizers.
SPILLS AND LEAKS: CAUTION: Floor may become slippery. Sweep/soak up small spills using inert material. For large spills, limit access to area. Dike and contain spill with inert material, if necessary, and transfer the material to containers suitable for recovery/disposal. Keep large spills out of sewers and open bodies of water.
WASTE DISPOSAL: Dispose of in accordance with all Federal, State and Local Environmental Laws in effect at the time.

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which maybe the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer or his agent based on its own studies and on the work of others. Neither the manufacturer nor his agent makes any warranty, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. Neither the manufacturer nor his agent shall be held liable (regardless of fault) to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

Data is supplied for use only in connection with occupational safety and health.