

SM1 SPRAY MASK

SM1 Liquid Spray Mask is fast drying clear film that prevents paint and primer overspray from adhering to vehicles, paint booth walls etc. SM1 is ready-to-use and can be applied in one uniform coat with all types of spray guns. SM1 can be peeled off or can be quickly rinsed off with clean water. SM1 is user friendly and contains no solvents. Because no solvents or harsh chemicals are used SM1 is completely safe to the environment.

Features:

1. Solvent Free - Zero V.O.C. - water based - environmentally safe
2. Protects entire vehicle unlike plastic sheeting
3. Seals down most dirt and dust
4. Dries clear so vehicle can still be driven in shop
5. Instantly dissolves with water when painting, buffing, or other work is completed.
6. Will not remove existing wax or polish
7. Dries in approximately 20-30 minutes
8. Can be baked at 170°F for up to 8 hours

Surface Preparation:

Apply on vehicles before they are exposed to paint overspray. Apply to inside walls and windows of spray booths to prevent overspray build up. Coating should be removed and re-applied to spray booth approximately every 2 weeks.

Remove all loose dust and dirt with air hose or cloth, mask around repair area with 12" masking paper. Fold paper over repair area and apply spray mask to remainder of vehicle in one wet coat. Fold masking paper back over spray mask when dry and fasten with masking tape.

Application Instructions:

Apply one full wet coat using the following gum setup as a guide. Conventional gun 1.8-2.0 mm tip 40-50 PSI, 1.6-2.0 mm tip 35-45 PSI, HVLP Gun 1.8-2.0 mm tip 25-45 PSI.

Cleaning:

Spray guns that do not have stainless or brass internal part may corrode if not cleaned and dried after each use. Clean with water and dry thoroughly before storing.