

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20
Version: 1.1Page: 1/10
(30253797/CDU_GEN_US/EN)

1. Substance/preparation and company identification

CompanyBASF CORPORATION
100 Campus Drive
Florham Park, NJ 0793224 Hour Emergency Response InformationCHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS Number	Content (weight%)
dimethyl ether	115-10-6	25 - 35
PEL/TLV not established		
acetone	67-64-1	10 - 20
OSHA PEL 1000 ppm 2400 mg/m ³		
ACGIH STEL 750 ppm; TWA 500 ppm		
epoxy resin	25036-25-3	5 - 15
PEL/TLV not established		
barium sulfate	7727-43-7	5 - 15
OSHA PEL 5 mg/m ³ R; PEL 15 mg/m ³ T		
ACGIH TWA 10 mg/m ³		
zinc phosphate	7779-90-0	1 - 10
PEL/TLV not established		
methyl amyl ketone	110-43-0	1 - 10
OSHA PEL 100 ppm 465 mg/m ³		
ACGIH TWA 50 ppm		
wollastonite (naturally occurring substance)	13983-17-0	1 - 10
PEL/TLV not established		
titanium dioxide	13463-67-7	1 - 10
OSHA PEL 15 mg/m ³ T		
ACGIH TWA 10 mg/m ³		
alkylated phenolic polyamine	proprietary	0 - 5
PEL/TLV not established		
propyl acetate	109-60-4	0 - 5
OSHA PEL 200 ppm 840 mg/m ³		
ACGIH STEL 250 ppm; TWA 200 ppm		
n-butyl acetate	123-86-4	0 - 5
OSHA PEL 150 ppm 710 mg/m ³		
ACGIH STEL 200 ppm; TWA 150 ppm		
talc	14807-96-6	0 - 5
ACGIH TWA 2 mg/m ³		
titanium dioxide	1317-80-2	0 - 5
PEL/TLV not established		

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Page: 2/10

Version: 1.1

(30253797/CDU_GEN_US/EN)

xylene 1330-20-7 0 - 5
OSHA PEL 100 ppm 435 mg/m3
ACGIH STEL 150 ppm; TWA 100 ppm

R Respirable fraction

T Total dust

3. HAZARD IDENTIFICATION

HMIS III RATING

Health: 2^a Flammability: 4 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

EMERGENCY OVERVIEW

WARNING

EXTREMELY FLAMMABLE

COMPRESSED GAS

FLAMMABLE LIQUID

FLAMMABLE AEROSOL

HARMFUL IF INHALED

CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE

CAN CAUSE LIVER DAMAGE

CAN CAUSE KIDNEY DAMAGE

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

MAY CAUSE PULMONARY EDEMA

INGESTION MAY CAUSE GASTRIC DISTURBANCES

POTENTIAL HEALTH EFFECTS

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Solvents are absorbed through the skin.

Acute toxicity:

Inhalation may cause CNS depression, blurred vision, dizziness and drowsiness.

Overexposure may cause nausea and vomiting.

Inhalation causes headache and nausea.

Gases have a suffocating effect.

Rapid vapourization of the liquid may cause frostbite on exposed tissues.

Eye contact may result in burns and permanent injury.

Vapors have a suffocating effect.

Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Information on: 2-heptanone

Inhalation of 2-heptanone (methyl amyl ketone) may lead to upper respiratory tract irritation and central nervous system

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Page: 3/10

Version: 1.1

(30253797/CDU_GEN_US/EN)

effects like headache, nausea and dizziness.

Information on: acetone

Acute exposures to relatively large amounts of acetone can result in local effects, such as irritation to eyes, nose, throat, and respiratory tract as well as systemic effects such as central nervous system (CNS) depression, which can range in severity from lightheadedness to loss of consciousness depending on the magnitude and length of the exposure.

Information on: allergic reaction

This product may cause allergic skin reaction.

Information on: n-butyl acetate

Inhalation of butyl acetate vapors may result in headache, dizziness, nausea, irritation of the respiratory tract, and CNS depression. Prolonged inhalation exposures have been known to produce upper respiratory tract irritation and acute transient signs of reduced activity at concentrations at 1500 ppm and above in rats, with no cumulative neurotoxic effects. Overexposure may cause irritation of the eyes, nose and throat.

Information on: barium sulfate

Ingestion of soluble barium salts produces muscle stimulation, followed by severe gastric disturbances, increased blood pressure, and central nervous system effects.

Information on: propyl acetate

Acute overexposure to propyl acetate may be highly irritating to the eyes, nose and throat and cause cough. Acute inhalation to high vapor concentrations may produce CNS effects, weakness, dizziness, nausea, vomiting and loss of consciousness.

Information on: talc

Acute exposures to high concentrations of talc may produce cough, dyspnea, chest pain and weakness.

Information on: wollastonite

This product contains wollastonite. Inhalation may result in irritation of the mucous membranes. Cough and difficulty breathing are possible. Ingestion may result in nausea, vomiting and diarrhea.

Information on: xylene

Aspiration of xylene may result in chemical pneumonitis, pulmonary edema and hemorrhage. Ingestion and skin absorption may lead to CNS depression, symptoms may include nausea, dizziness and blurred vision.

Information on: zinc oxide

Inhalation of zinc dusts may result in respiratory irritation. Inhalation of zinc fumes may cause "metal fume fever". Symptoms of metal fume fever include metallic taste, dryness, and irritation of the throat, difficult breathing, weakness, fatigue and fever.

Irritation:

Skin contact may result in irritation, defatting and dermatitis. Vapors cause irritation to the respiratory tract and the eyes. Prolonged inhalation of product vapor can result in irritation of the mucous membranes.

Information on: epoxy resin

Prolonged or repeated contact with the eyes and skin may result in irritation. This material contains epoxy resins

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Page: 4/10

Version: 1.1

(30253797/CDU_GEN_US/EN)

which may result in skin irritation or sensitization after repeated contact. Ingestion of the solid may result in gastric disturbances.

Repeated dose toxicity:

Information on: 2-heptanone

Repeated inhalation exposures to 2-heptanone (methyl amyl ketone) have been known to produce neurological effects in experimental animals at 1000 ppm. Repeated oral exposures in rats have been known to produce liver and kidney effects at 500 mg/kg/day.

Information on: acetone

High doses of acetone (500 and 2500 mg/kg/day) administered by oral gavage to rats for 90 consecutive days resulted in some clinical chemistry and blood changes as well as increased absolute/relative liver and kidney weights. Histopathological examination of both organs showed acetone did not affect the liver but appeared to accentuate the kidney changes which accompany aging. No effects were observed at 100 mg/kg/day. Chronic occupational exposures to acetone at levels ranging from 300 to 100 ppm have reportedly been associated with irritation and mild CNS effects but have not affected clinical chemistry parameters or worker mortality.

Information on: n-butyl acetate

In a teratogenicity study, pregnant rabbits were exposed to n-butyl acetate vapors at 0 or 1500 ppm from day 1 to day 19 of gestation; pregnant rats were exposed at the same concentrations from day 1 to day 16 of gestation. Body weight changes were observed in the rats but not the rabbits. Reproductive performance was not affected. Rabbit fetus size was not affected by exposure, but fetal size in all exposed groups of rats was reduced, suggesting embryotoxicity.

Information on: talc

Prolonged or repeated exposure to talc can result in a form of pulmonary fibrosis (talc pneumoconiosis), possibly due to asbestos content. In a National Toxicology Program (NTP) inhalation study, talc exhibited some evidence of carcinogenicity in male rats, clear evidence in female rats and no evidence in mice. It is thought that the effects, which were reported at the high dose, were due to overburdening of the lungs.

Information on: titanium dioxide

In a National Cancer Institute (NCI) feeding study, titanium dioxide was not carcinogenic to rats or mice at maximum tolerated doses. In another study, TiO₂ caused fibrosis and lung cancer in rats exposed to 250 mg/m³ by inhalation. However, no effects were seen at lower airborne concentrations.

Information on: wollastonite

This product contains wollastonite. In a lifetime inhalation study, rats exposed to 10 mg/m³ wollastonite exhibited a slightly toxic lung response; however, this was reversible after exposure was stopped. Exposure to wollastonite from this product is not anticipated unless the product is used in secondary mechanical processing operations which form dusts.

Information on: xylene

The chronic effects of overexposure to xylene include possible liver and kidney damage. A mixture of o, m, and p-xylenes was

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 5/10

(30253797/CDU_GEN_US/EN)

teratogenic and embryo toxic to mice by the oral route; however, these effects were accompanied by maternal toxicity. Rats exposed to 1000 mg/m³ by inhalation exhibited no teratogenic effects; however, minor skeletal abnormalities occurred.

Information on: zinc oxide

Thirteen of nineteen workers in zinc powder factory were reported to exhibit inflammation of the upper respiratory tract after 2 to 3 years of employment. Limited studies on the developmental toxicity of zinc oxide in animals indicate that doses as high as 200 mg/kg have caused reduced fetal body weight and fetal death.

4. FIRST-AID MEASURES

General advice:

Remove contaminated clothing.

Contact the local poison control center or call BASF Emergency Response at 1-800-832-HELP (4357).

If inhaled:

Keep patient calm, remove to fresh air.

If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Wash affected areas with water for at least 15 minutes.

If irritation develops, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes.

Hold eyelids open to facilitate rinsing.

Seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water.

Do not induce vomiting due to aspiration hazard.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Immediate medical attention is required.

Ingestion may cause irritation of the gastrointestinal tract.

Aspiration may result in chemical pneumonitis, which may be fatal.

5. FIRE FIGHTING MEASURES

Flash point: < 1 °F (< 17.2- °C) (calculated)

Lower explosion limit: 1.1 VOL%

Upper explosion limit: 18.0 VOL%

Suitable extinguishing media:

Dry extinguishing media

Carbon dioxide

Foam

Unsuitable extinguishing media for safety reasons:

Water spray

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 6/10
(30253797/CDU_GEN_US/EN)

Hazards during firefighting:

Flammable gases/vapors.

Aerosol container contains flammable gas under pressure.

Vapors and/or decomposition products are irritants and/or toxic.

If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Protective equipment for firefighting:

Wear self-contained breathing apparatus and turn-out gear.

Further information:

Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Flash fire may occur.

Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat.

Do not flood burning material with water due to potential spreading of fire.

Contain contaminated water/firefighting water.

Run-off water from fire may cause pollution.

Notify proper authorities.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Extinguish sources of ignition nearby and downwind.

Wear suitable personal protective clothing and equipment.

Ensure adequate ventilation.

Avoid prolonged inhalation.

Avoid contact with skin and eyes.

Use antistatic tools.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Acutely toxic for aquatic organisms.

Cleanup:

Dike spillage.

Place into appropriately labeled waste containers.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. HANDLING AND STORAGE

HANDLING

General advice:

Ensure adequate ventilation.

Do not puncture, drop or slide containers.

Use static lines when mixing and transferring material.

Handle and open container with care.

Avoid contact with the skin, eyes and clothing.

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 7/10

(30253797/CDU_GEN_US/EN)

WARNING: Empty containers may still contain hazardous residue.
Do not apply to hot surfaces.
Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces.

Protection against fire and explosion:

Use antistatic tools.

Exhaust fans should be explosion proof.

Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources.

Sealed containers should be protected against heat as this results in pressure build-up.

Risk of explosion if heated under confinement.

Avoid all sources of ignition: heat, sparks, or open flame.

STORAGE

General advice:

Keep container tightly closed.

Protect from direct sunlight.

Protect from temperatures above 49C/ 120F.

Consult local fire marshal for storage requirements.

Storage incompatibility:

General: Segregate from incompatible substances.

Segregate from oxidizing agents.

Segregate from strong bases.

Segregate from strong acids.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

See section 2.

ADVICE ON SYSTEM DESIGN

Provide local exhaust ventilation to maintain recommended P.E.L.

General mechanical ventilation should comply with OSHA 1910.94.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Wear NIOSH-certified (or equivalent) organic vapor respirator.

Particulate filters should be added during spray operations.

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 8/10
(30253797/CDU_GEN_US/EN)

Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen based on activity level and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and eye wash.

Contact lenses should not be worn.

Remove contaminated clothing.

Contaminated equipment or clothing should be cleaned after each use or disposed of.

Hands and/or face should be washed before breaks and at the end of the shift.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: aerosol

Odour: Ketone

Colour: Gray

Boiling range: 13- - 300 °F / 25.0- - 148.9 °C

Vapour pressure: not available

Weight per gallon: 8.72 lb/gal CALC

Vapour density: heavier than air

Solids content: approx. 47 %

% volatiles: approx. 77.0 VOL%

10. STABILITY AND REACTIVITY

Conditions to avoid:

Avoid all sources of ignition: heat, sparks or open flames.

Avoid electrostatic discharge.

Substances to avoid:

Strong bases

Strong oxidizing agents

Strong acids

Hazardous reactions:

This product is chemically stable.

Decomposition products:

Carbon monoxide

Carbon dioxide

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 9/10
(30253797/CDU_GEN_US/EN)

13. DISPOSAL CONSIDERATIONS

Waste disposal of substances:

Dispose of in accordance with national, state and local regulations.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste.

It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA.

Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA licensed facility.

Do not incinerate closed containers.

Contaminated packaging:

WARNING: Empty containers may still contain hazardous residue.

Facility must be capable of handling empty aerosol cans.

Do not cut, puncture, crush, or incinerate empty aerosol containers.

Dispose of in accordance with national, state and local regulations.

14. TRANSPORT INFORMATION

Reference Bill of Lading.

15. REGULATORY INFORMATION

FEDERAL REGULATIONS

TSCA, US released / listed

SARA 313:

CAS number	Weight%	Chemical name
7779-90-0	7.7	zinc phosphate
1330-20-7	1.4	xylene

STATE REGULATIONS

State RTK:

CAS Number	Chemical name
115-10-6	dimethyl ether
67-64-1	acetone
25036-25-3	epoxy resin
7727-43-7	barium sulfate
7779-90-0	zinc phosphate
110-43-0	methyl amyl ketone
13983-17-0	wollastonite (naturally occurring substance)
13463-67-7	titanium dioxide
489909-5285-P-NLR	alkylated phenolic polyamine
109-60-4	propyl acetate
123-86-4	n-butyl acetate
14807-96-6	talc
1317-80-2	titanium dioxide

Safety data sheet

AM2759 2K Epoxy Primer

Revision date : 2007/04/20

Version: 1.1

Page: 10/10
(30253797/CDU_GEN_US/EN)

1330-20-7

xylene

California Proposition 65 information:

WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

16. OTHER INFORMATION

Recommended use: FOR INDUSTRIAL USE ONLY.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.