

PRODUCT: *Quantum*[™] 10:1 BPO Catalyst – High Temp

PART NUMBER: 100458 **2.8 oz. Tube** **12 units per case** **3 lbs. per case**

DESCRIPTION: Quantum 10:1 BPO catalyst utilizes patent-pending technology that provides unsurpassed performance when mixed with Quantum fillers and putties. It is specially engineered to provide optimum performance in temperatures above 80°F/26°C, without under catalyzing the product. It also provides end users with a more forgiving mix ratio for a more uniform mix.

FEATURES & BENEFITS:

Feature	Benefit
Engineered to provide optimum performance in temperatures above 80°F	Eliminates need to under-catalyze due to warm climates and eliminates paint issues associated with under-catalyzing.
10:1 Mix Ratio	Provides easier and more uniform mixing, ensuring consistent, uniform curing.
Epoxy enriched	Enhanced sanding characteristics, increased corrosion resistance and eliminates shrinkage.

MIXING:

- Place desired amount of filler or putty on a clean, non-fibrous mixing board.
- Knead the Quantum 10:1 BPO Catalyst tube.
- Measure catalyst 10% by volume (add a ribbon of Quantum BPO catalyst edge to edge across the center of 4" diameter puddle of filler/putty). Puddles larger than 4" in diameter will require additional hardener.
- Fold catalyst into filler/putty until uniform color is achieved.

TECHNICAL SPECIFICATIONS:

- | | |
|------------------------|-------------------------------|
| • Appearance | Red colored paste |
| • VOC | Packaged: 0.0 lbs/gal (0 g/L) |
| • Weight per Gallon | 7.72 lbs/gal |
| • Contents and Caution | MSDS available upon request |

NOTE: Properties are typical values and should not be considered as sales specifications.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat products. Material Safety Data Sheets can be found online at www.evercoat.com.

NOTES: Keep container closed and store in a cool dry place