EVERCOAT®

PRODUCT INFORMATION SHEET

PRODUCT: **Quantum™ 10:1 BPO Catalyst – Low Temp**

PART NUMBER: 100**457** **2.8 oz. Tube** **12 units per case** **3 lbs. per case**

DESCRIPTION: Quantum 10:1 BPO catalyst utilizes patent-pending technology that provides unsurpassed performance when mixed with Quantum fillers and putties. It is specially engineered to provide optimum performance in temperatures below 80°F/26°C, without over catalyzing the product. It also provides end users with a more forgiving mix ratio for a more uniform mix.

FEATURES & BENEFITS:

Feature	Benefit
Engineered for optimum performance below 80°F	Eliminates need to over-catalyze due to cold climates and eliminates paint issues associated with over-catalyzing.
10:1 Mix Ratio	Provides easier and more uniform mixing, ensuring consistent, uniform curing.
Epoxy enriched	Enhanced sanding characteristics, increased corrosion resistance and reduces shrinkage.

MIXING:

- Place desired amount of filler or putty on a clean, non-fibrous mixing board**.**
- Knead the Quantum 10:1 BPO Catalyst tube.
- Measure catalyst 10% by volume (add a ribbon of Quantum BPO catalyst edge to edge across the center of 4” diameter puddle of filler/putty). Puddles larger than 4” in diameter will require additional hardener.
- Fold catalyst into filler/putty until uniform color is achieved.

TECHNICAL SPECIFICATIONS:

▪ Appearance	Blue colored paste
▪ VOC	Packaged: 0.0 lbs/gal (0 g/L)
▪ Weight per Gallon	7.31 lbs/gal
▪ Contents and Caution	MSDS available upon request

NOTE: **Properties are typical values and should not be considered as sales specifications.**

SAFETY & HANDLING: Read all directions and warnings prior to using Evercoat products. Material Safety Data Sheets can be found online at www.evercoat.com.

NOTES: Keep container closed and store in a cool dry place