

**DuPont Performance Coatings**  
**MATERIAL SAFETY DATA SHEET**  
**ChromaPremier® 42400S™ 2K Premier Translucent Sealer**  
**ChromaPremier® 12305S™ Activator**  
**ChromaPremier® 42455S™, 42475S™, 42495S™ Reducers**

<b>SECTION 1 - Product and Company Identification</b>		<b>INGREDIENTS</b>	<b>CAS #</b>	<b>VAPOR PRESSURE</b>	<b>EXPOSURE LIMITS</b>
Manufacturer:	E.I. duPont de Nemours & Co. Dupont Performance Coatings Wilmington, DE, 19898	DIISOBUTYL KETONE	108-83-8	1.8	A 25.0 ppm O 50.0 ppm
Telephone:	Product Information: (800) 441-7515 Medical Emergency: (800) 441-3637 Transportation Emergency: (800) 424-9300 (CHEMTREC)	ETHYL ACETATE	141-78-6	93.2@25.0°C	A 400.0 ppm O 400.0 ppm
Product:	<b>ChromaPremier® 42400S™ 2K Premier Translucent Sealer</b> <b>ChromaPremier® 12305S™ Activator</b> <b>ChromaPremier® 42455S™, 42475S™, 42495S™ Reducers</b>	ETHYL 3-ETHOXY PROPIONATE	763-69-9	1.1@25.0°C	A None O None
DOT Shipping Name:	See DOT addendum.	ETHYLBENZENE	100-41-4	7.0	A 125.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 25.0 ppm 8 & 12 hour TWA
Hazardous Materials Information:	See Section 10.				

**SECTION 2 - Composition, Information on Ingredients**

<b>INGREDIENTS</b>	<b>CAS #</b>	<b>VAPOR PRESSURE</b>	<b>EXPOSURE LIMITS</b>	<b>INGREDIENTS</b>	<b>CAS #</b>	<b>VAPOR PRESSURE</b>	<b>EXPOSURE LIMITS</b>
ACETONE	67-64-1	247.0@68.0°F	A 750.0 ppm 15 min STEL A 500.0 ppm O 1000.0 ppm D 500.0 ppm 8 & 12 hour TWA	GAMMA-GLYCIDOXYPROPYLTRIMETHOXYSILIANE	2530-83-8	1.0	A None O None
ACRYLIC POLYMER	63150-02-7	None	A None O None	METHYL AMYL KETONE	110-43-0	3.4	A 50.0 ppm O 100.0 ppm
ALIPHATIC POLYAMINE	54914-37-3	None	A None O None	N-PENTYL PROPIONATE	624-54-4	1.5	A None O None
ALIPHATIC POLYISOCYANATE RESIN	28182-81-2	None	S 1.0 mg/m <sup>3</sup> 15 min STEL S 0.5 mg/m <sup>3</sup> A None O None	POLYSILOXANE	Not Avail	2.0@25.0°C	A None O None
BUTYL ACETATE	123-86-4	10.0	A 200.0 ppm 15 min STEL A 150.0 ppm O 150.0 ppm	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	3.8	D 10.0 ppm 8 & 12 hour TWA A None O None
CERAMIC MICROSPHERES	66402-68-4	None	A 10.0 mg/m <sup>3</sup> O 15.0 mg/m <sup>3</sup>	TOLUENE	108-88-3	22.0	O 300.0 ppm CEIL O 500.0 ppm 10 min TWA O 200.0 ppm D 50.0 ppm 8 & 12 hour TWA A 50.0 ppm Skin
				XYLENE	1330-20-7	8.0@25.0°C	A 150.0 ppm



# Product Launch MSDS

## July 2005

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
			15 min STEL D 150.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 100.0 ppm 8 & 12 hour TWA
ZINC PHOSPHATE	7779-90-0	None	O 5.0 mg/m <sup>3</sup> Respirable Dust A None
1,6-HEXAMETHYLENE DIISOCYANATE	822-06-0	0.0@25.0°C	A 5.0 ppb O None
4,6-DIMETHYL-2-HEPTANONE	19549-80-5	None	A None O None

\*A=ACGIH, O=OSHA, D=DuPont, S=Suppliers. Limits are 8 hour TWA unless otherwise specified. Vapor pressure @25°C unless otherwise noted.

### SECTION 3 - Hazards Information

#### Potential Health Effects:

##### Inhalation:

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product contains or is mixed with an isocyanate activator/hardener, the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

##### Ingestion:

May result in gastrointestinal distress.

##### Skin or eye contact:

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

#### Other Potential Health Effects in addition to those listed above:

##### ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

##### ALIPHATIC POLYAMINE

Repeated or prolonged skin contact may cause any of the following: skin sensitization.

##### ALIPHATIC POLYISOCYANATE RESIN

Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure.

The following medical conditions may be aggravated by exposure: asthma, skin disorders, respiratory disorders. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Skin or eye contact may cause any of the following: irritation.

##### BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

##### DIISOBUTYL KETONE

The following medical conditions may be aggravated by exposure: asthma, blood, dermatitis. Contact may cause skin irritation with discomfort or rash. Repeated exposure may cause allergic skin rash, itching, swelling. This substance may cause damage to any of the following organs/systems: eyes, kidneys, liver. Extremely high oral and inhalation doses in laboratory animals have shown weight changes in various organs such as the liver, kidney, brain, heart and adrenal gland. In addition, liver and kidney injury were observed at the extremely high inhalation level. In another inhalation study there was a slight depression in the white blood cell count. Liquid or vapor causes irritation, experienced as stinging, excess blinking and tear production, with excess redness and swelling of the conjunctiva.

##### ETHYL ACETATE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

##### ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

##### PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Recurrent overexposure may result in liver and kidney injury.

##### TOLUENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heartbeats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

##### XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing

# Product Launch MSDS

## July 2005



# Product Launch MSDS

## July 2005

fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

### 1,6-HEXAMETHYLENE DIISOCYANATE

Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure. The following medical conditions may be aggravated by exposure: asthma, skin disorders, respiratory disorders. Overexposure may cause damage to any of the following organs/systems: lungs, skin. Can result in irritation and possible corrosive action in the mouth, stomach tissue and digestive tract. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Skin or eye contact may cause any of the following: irritation.

### SECTION 4 - First Aid Measures

#### First Aid Procedures:

##### Inhalation:

If affected by inhalation of vapor or spray mist, move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulty persists, or occurs later, consult a physician.

##### Ingestion:

In the unlikely event of ingestion, DO NOT INDUCE VOMITING. Call a physician immediately and have names of ingredients available.

##### Skin or eye:

In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, contact a physician.

### SECTION 5 - Firefighting Measures

**Flash Point (Closed Cup)** See Section 11 for exact values.

**Flammable limits** LFL 0.8 % UFL 13.1 %

#### Extinguishing media:

Universal aqueous film-forming foam, carbon dioxide, dry chemical.

#### Fire fighting procedures:

Full protective equipment, including self-contained breathing apparatus, is recommended. Water from fog nozzles may be used to prevent pressure build-up.

#### Fire & explosion hazards:

For flammable liquids, vapor/air will ignite when an ignition source is present. In other cases, when heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

### SECTION 6 - Accidental Release Measures

#### Steps to be taken in case material is released or spilled:

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. If the material contains, or is mixed with an isocyanate activator/hardener: Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TMN 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance) Pressure can be generated. Do not seal waste containers for 48 hours to allow CO<sub>2</sub> to vent. After 48 hours, material may be sealed and disposed of properly. If material does not contain or is not mixed with an isocyanate activator/hardener: Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye

protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

### SECTION 7 - Handling and Storage

#### Precautions to be taken in handling and storing:

Observe label precautions. If combustible (flashpoint between 100 - 200°F), keep away from heat, sparks and flame. If flammable (flashpoint less than 100°F), also keep away from static discharges and other sources of ignition. If material is extremely flammable (flashpoint less than 20°F) or flammable, VAPORS MAY IGNITE EXPLOSIVELY OR CAUSE FLASH FIRE, respectively. Vapors may spread long distances. Prevent buildup of vapors. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120°F. If product is waterbased, do not freeze.

#### Other precautions:

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved respirator or appropriate ventilation, and gloves.

### SECTION 8 - Exposure Controls or Personal Protection

#### Engineering controls and work practices:

##### Ventilation:

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable exposure limits.

##### Respiratory:

Do not breathe vapors or mists. If this product contains isocyanates or is used with an isocyanate activator/hardener, wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with paint, during application and until all vapors and spray mist are exhausted. If product does not contain or is not mixed with an isocyanate activator/hardener, a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH TC-23C) and particulate filter (NIOSH TC-84A) may be used. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed vapor or spray mist if product contains or is mixed with isocyanate activators/hardeners.

##### Protective clothing:

Neoprene gloves and coveralls are recommended.

##### Eye protection:

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

### SECTION 9 - Physical and Chemical Properties

Evaporation Rate	Slower than Ether
Solubility in water	NIL
Vapor Density	Heavier than air
Approx. boiling range (°C)	77 - 140 (°C)
Approx. freezing range (°C)	-92 - -49 (°C)
Gallon weight (lbs/gal)	7.36 - 10.09
Specific gravity	0.88 - 1.21
Percent volatile by volume	43.07 - 82.25
Percent volatile by weight	35.00 - 82.49
Percent solids by volume	17.75 - 56.94
Percent solids by weight	17.51 - 65.00

# Product Launch MSDS

## July 2005



# Product Launch MSDS

July 2005

## SECTION 10 - Stability and Reactivity

**Stability:** Stable  
**Incompatibility (materials to avoid):** water, alcohols, amines  
**Hazardous decomposition products:**  
CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.  
**Hazardous polymerization:** Will not occur.  
**Sensitivity to static discharge:**  
For flammable materials (flashpoint less than 100°F) and combustibles (flashpoint between 100-200°F) if heated above the flashpoint, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.  
**Sensitivity to mechanical impact:** Not Applicable

## SECTION 11 - Additional Information

### PRODUCT CODE                      INGREDIENTS (Product Specific)

**42400S™** acetone, acrylic polymer, butyl acetate, ceramic microspheres, diisobutyl ketone, ethylbenzene(0.6-1.6%\*<sup>@</sup>), gamma-glycidoxypropyltrimethoxysilane, methyl amyl ketone, polysiloxane, propylene glycol monomethyl ether acetate, xylene(5-6%\*<sup>@</sup>), zinc phosphate(12%\*), 4,6-dimethyl-2-heptanone

**GAL WT: 10.09 WT PCT SOLIDS: 56.49 VOL PCT SOLIDS: 38.26**  
**SOLVENT DENSITY: 7.11    VOC LE: 4.3    VOC AP: 4.1**  
**FLASH POINT: 20°F to below 73°F    H: 2 F: 3 R: 0    OSHA STORAGE: IB**  
**TSCA STATUS: In compliance    PHOTOCHEMICALLY REACTIVE: YES**

**12305S™** aliphatic polyisocyanate resin, butyl acetate, diisobutyl ketone, methyl amyl ketone, 1,6-hexamethylene diisocyanate(0.1%\*<sup>@</sup>), 4,6-dimethyl-2-heptanone

**GAL WT: 8.45 WT PCT SOLIDS: 65.00 VOL PCT SOLIDS: 56.94**  
**SOLVENT DENSITY: 6.87    VOC LE: 3.0    VOC AP: 3.0**  
**FLASH POINT: 73°F to below 100°F    H: 2 F: 3 R: 1    OSHA STORAGE: IC**  
**TSCA STATUS: In compliance    PHOTOCHEMICALLY REACTIVE: NO**

**42455S™** aliphatic polyamine, butyl acetate, ethyl acetate, ethylbenzene(0.8-2.1%\*<sup>@</sup>), toluene(25-25%\*<sup>@</sup>), xylene(6-7 %\*<sup>@</sup>)

**GAL WT: 7.36 WT PCT SOLIDS: 17.56 VOL PCT SOLIDS: 17.75**  
**SOLVENT DENSITY: 7.38    VOC LE: 6.1    VOC AP: 6.1**  
**FLASH POINT: 20°F to below 73°F    H: 3 F: 3 R: 1    OSHA STORAGE: IB**  
**TSCA STATUS: In compliance    PHOTOCHEMICALLY REACTIVE: YES**

**42475S™** aliphatic polyamine, n-pentyl propionate, propylene glycol monomethyl ether acetate

**GAL WT: 7.68 WT PCT SOLIDS: 17.55 VOL PCT SOLIDS: 18.51**  
**SOLVENT DENSITY: 7.78    VOC LE: 6.3    VOC AP: 6.3**  
**FLASH POINT: 100°F - 141°F    H: 3 F: 2 R: 1    OSHA STORAGE: II**  
**TSCA STATUS: In compliance    PHOTOCHEMICALLY REACTIVE: NO**

**42495S™** aliphatic polyamine, ethyl 3-ethoxy propionate, n-pentyl propionate, propylene glycol monomethyl ether acetate

**GAL WT: 7.52 WT PCT SOLIDS: 17.51 VOL PCT SOLIDS: 18.09**  
**SOLVENT DENSITY: 7.58    VOC LE: 6.2    VOC AP: 6.2**  
**FLASH POINT: 100°F - 141°F    H: 3 F: 2 R: 1    OSHA STORAGE: II**  
**TSCA STATUS: In compliance    PHOTOCHEMICALLY REACTIVE: NO**

## Footnotes:

**TSCA: in compliance** = In compliance with TSCA Inventory requirements for commercial purposes.

**ACGIH** = American Conference of Government Industrial Hygienists.

**IARC** = International agency for Research on Cancer.

**NTP** = National Toxicology Program.

**OSHA** = Occupational Safety and Health Administration.

**PNOR** = Particles Not Otherwise Regulated.

**PNOC** = Particles Not Otherwise Classified.

**STEL** = Short Term Exposure Limit.

**TWA** = Time Weighted Average.

**TM** = Is a Trademark of E.I. du Pont de Nemours & Co.

\* = Section 313 Supplier Notification: These chemicals are subject to the reporting requirements of Section 313 of the Emergency planning and Right-to-Know act of 1986 and of 40 CFR 372.

@ = Clean Air Act Hazardous Air Pollutant.

# = EPCRA Section 302 - Extremely Hazardous Substance.

## NOTICE:

The information on this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

## Product Manager - Refinish Sales

Prepared by: M. C. Gangi

# Product Launch MSDS

July 2005

© 2005 E.I. du Pont de Nemours and Company. All rights reserved.  
Reproduction or translation of any part of this work beyond that permitted by U.S. copyright laws without the written permission of DuPont is unlawful and strictly forbidden.



*The miracles of science™*