

ColorBalancer Aerosol Technical Data Sheet

Description

ColorBalancer aerosol products come in four (4) different shades;

- **CB100** – Darkens white colors
- **CB101** – Darkens light colors
- **CB102** – Darkens medium colors
- **CB103** – Darkens dark colors

ColorBalancer is a patent pending, point of delivery color matching aid that is designed to assist in the color tinting of adjacent panels to achieve color match acceptance as well as a color adjusting topcoat.


Application

Use only in a well ventilated area.



1.) Preparation

Area to be sprayed should be cleaned using **CBC Cleaner**. **CBC Cleaner** chemically cleans and prepares the surface for adhesion without the need for sanding.



2.) Mask

Mask surrounding area to be sprayed using 12" paper to reduce overspray.



3.) Spray

Shake the **ColorBalancer Aerosol Product** vigorously for 30 seconds. Hold 8" to 10" from surface, spray in light and even strokes. Allow ten (10) minutes dry time at 70° F. Do not recoat. When finished, turn can upside down and press sprayhead for about 3 seconds to clear the valve.




4.) Hand Buff

If needed, hand buff perimeter of sprayed area.

TIPS

If application of **ColorBalancer Aerosol Product** does not achieve color acceptability after one application, spray affected area with **CBR Remover**. Wipe away **ColorBalancer Aerosol Product** with a soft, clean cloth. After removal process, re-clean with **CBC Cleaner** before reapplying **ColorBalancer Aerosol Products**. Choose the correct shade **ColorBalancer Aerosol Product** and follow label's instructions for application.

Flash/Dry Times



Allow Ten Minutes at 70° F for product to dry.

VOC Regulated Areas

These directions refer to the use of products which may be restricted in VOC regulated areas. Follow usage recommendations in the VOC Compliant Products Chart for your area.

Safety and Handling

Before using any ColorBalancer Product, be sure to read all safety directions and warnings. WEAR A PROPERLY FITTED AIR PURIFYING RESPIRATOR with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A), eye protection, gloves and protective clothing during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air purifying respirator fit is not possible, wear a positive-pressure, supplied air respirator (NIOSH TC-19). In all cases follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. This product is intended for industrial use only by professional, trained painters.

Please visit: www.SpectrumDetails.com to view or print an additional copy of this "Technical Data" sheet.